



Product Service

CERTIFICATE

No. Z2 102627 0023 Rev. 14

Holder of Certificate: **DAS SOLAR CO., LTD.**
No. 43, South Bailing Road
324022 Quzhou City, Zhejiang Province
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062107114-14

Valid until: 2030-06-18

Date, 2025-06-20

(Zhulin Zhang)

CERTIFICATE

No. Z2 102627 0023 Rev. 14

Model(s):

DAS-DH156PA-xxx, xxx=570 to 610 in step of 5;
 DAS-DH144PA-xxx, xxx= 510 to 565 in step of 5;
 DAS-DH132PA-xxx, xxx= 470 to 515 in step of 5;
 DAS-DH120PA-xxx, xxx= 425 to 470 in step of 5;
 DAS-DH108PA-xxx, xxx= 385 to 425 in step of 5;
 DAS-DH156NA-xxx, xxx=585 to 665 in step of 5;
 DAS-DH144NA-xxx, xxx=530 to 610 in step of 5;
 DAS-DH132NA-xxx, xxx=485 to 550 in step of 5;
 DAS-DH120NA-xxx, xxx=445 to 500 in step of 5;
 DAS-DH108NA-xxx, xxx=400 to 460 in step of 5;
 DAS-DH156NA.A-xxx, xxx=585 to 665 in step of 5;
 DAS-DH144NA.A-xxx, xxx=530 to 610 in step of 5;
 DAS-DH132NA.A-xxx, xxx=485 to 550 in step of 5;
 DAS-DH120NA.A-xxx, xxx=445 to 500 in step of 5;
 DAS-DH108NA.A-xxx, xxx=400 to 460 in step of 5;
 DAS-DH144ND-xxx, xxx=580 to 620 in step of 5;
 DAS-DH108ND-xxx, xxx=435 to 465 in step of 5;
 DAS-DH132NE-xxx, xxx=580 to 650 in step of 5;
 DAS-DH132NE.A-xxx, xxx=580 to 650 in step of 5;
 DAS-DH96NE-xxx, xxx=420 to 470 in step of 5;
 DAS-DH96NE.A-xxx, xxx=420 to 470 in step of 5;
 DAS-DH108NE-xxx, xxx=475 to 530 in step of 5;
 DAS-DH108NE.A-xxx, xxx=475 to 530 in step of 5;
 DAS-DH120ND-xxx, xxx=485 to 515 in step of 5;
 DAS-DH132NC-xxx, xxx=685 to 745 in step of 5;
 DAS-DH132NC.A-xxx, xxx=685 to 745 in step of 5
 DAS-DH120NC-xxx, xxx=625 to 675 in step of 5;
 DAS-DH120NC.A-xxx, xxx=625 to 675 in step of 5
 DAS-DH132TE-xxx, xxx=610 to 655 in step of 5;
 DAS-DH96TE-xxx, xxx=445 to 475 in step of 5;
 DAS-DH156NF-xxx, xxx=715 to 740 in step of 5;
 DAS-WH156NA-xxx, xxx=580 to 650 in step of 5;
 DAS-WH144NA-xxx, xxx=535 to 600 in step of 5;
 DAS-WH132NA-xxx, xxx=490 to 550 in step of 5;
 DAS-WH120NA-xxx, xxx=445 to 500 in step of 5;
 DAS-WH108NA-xxx, xxx=400 to 450 in step of 5;
 DAS-WH156PA-xxx, xxx=575 to 610 in step of 5;
 DAS-WH144PA-xxx, xxx=530 to 565 in step of 5;
 DAS-WH132PA-xxx, xxx=485 to 515 in step of 5;
 DAS-WH120PA-xxx, xxx=440 to 470 in step of 5;
 DAS-WH108PA-xxx, xxx=400 to 425 in step of 5;
 DAS-WH132NE-xxx, xxx=605 to 635 in step of 5;
 DAS-WH108NE-xxx, xxx=495 to 520 in step of 5;
 DAS-WH96NE-xxx, xxx=440 to 460 in step of 5;
 DAS-WH132TE-xxx, xxx=610 to 655 in step of 5;
 DAS-WH96TE-xxx, xxx=445 to 475 in step of 5;
 xxx is standing for rated output power at STC



CERTIFICATE

No. Z2 102627 0023 Rev. 14

Parameters:	Construction:	Framed with Junction box, Cable and Connectors.
	Test Laboratory:	Changzhou HuaYang Inspection and Testing Technology Co., Ltd. B Area on 1/F., Building 12, C Area on 4/F., and A Area on 1/F., Building 10, No. 8, Lanxiang Road, West Taihu Science and Technology Industrial Park Changzhou Jiangsu China
	Safety Class:	Class II
	Fire Safety Class:	Class C according to UL790
	Maximum System Voltage:	1500 V DC

Tested according to:	IEC 61215-1:2021
	IEC 61215-2:2021
	IEC 61215-1-1:2021
	IEC 61730-1:2023
	IEC 61730-2:2023