

Type designation: MoogL160/ism

Article number: N5014907

Images



(Illustration similar)

Description

NH fuse-links, utilization category gG with combi indicator and isolated gripping lugs according to IEC 60269 respectively DIN EN 60269-1 and DIN VDE 0636-2 with a rated voltage of AC500V.

Features

Rated voltage AC:	500 V
Rated breaking capacity AC:	120 kA
Utilization category:	gG
Type:	MoogL160/ism
Class:	Ganzbereichssicherung, für allgemeine Anwendungen, hauptsächlich Kabel- und Leitungsschutz
Operating Joule integral 254V:	135,290 A²s
Operating Joule integral 440V:	211,300 A²s
Operating Joule integral 550V:	275,000 A²s
Pre-arcing Joule integral:	73600 A²s
Power dissipation at rated current:	11.2 W
Power dissipation at 70% rated current:	5.0 W
Size:	NH00
Rated current:	160 A
Product standard:	<ul style="list-style-type: none"> • IEC 60269-1 • IEC 60269-2 • DIN VDE 0636-2
Indicator / Signalling:	Combi indicator
Gripping lugs:	isolated
Contact type:	Blade contact
Packaging unit:	3
ETIM - Code:	EC000055

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 27.03.2026 / 14:37

Documents



Catalogue NH-fuse-links gG



Catalogue Appendix

