

Type designation: KETO-00-3/F

Article number: T500113002

Images



(Illustration similar)

Description

NH fuse-switch-disconnector KETO-00-3/F
according to EN60947-3,
size NH00 - 160A,
3pole for baseplate mounting
with universal terminal M8 x 16/2 x M5 cable terminal at top and bottom side

Features

Type:	KETO-00-3/F
Total power loss at I_{th} (without fuse-link) P_V :	9 W
Product Lifecycle:	Active product
Product description:	KETO-00-3/F
Rated operating voltage U_e :	690 V
Rated operating current I_e :	160 A
Product standard:	IEC/DIN EN60947-3
Conv. free air thermal current with fuse-links I_{th} :	160 A
Conv. free air thermal current with solid links:	250 A
Size:	NH00
Rated frequency:	50 - 60 Hz
Rated isolation voltage U_i :	1,000 V
Nominal current with fuse:	NH00-160A
Max. permissible power dissipation per fuse-link:	12 W
Power loss at 80% I_{th} (without fuse-link):	5.8 W
Rated conditional short-circuit current I_{cc} :	120 (AC 500V) kA
Rated impulse voltage U_{imp} :	8 kV
Rated short-time withstand current $I_{cw}(kA)$:	5
Utilization category 1:	690V - 160A - AC-21B
Utilization category 2:	400V - 160A - AC-23B
Utilization category 3:	250V - 160A - DC-22B
Ambient temperature:	-25 up to +70 (Attention derating of rated current required) °C
Altitude:	2000 m
Pollution degree:	3
Overvoltage category:	III
Mounting position:	vertical / horizontal
Electrical endurance (switching cycles):	200
Mechanical endurance (total switching cycles):	1,600

Material properties:	Unterteil: Temperaturbeständigkeit bis 125°C Selbstverlöschend nach UL94 Kriechstromfestigkeit CTI 600 Halogenfrei Schutzabdeckungen, Schaltdeckel: Temperaturbeständigkeit bis 125°C Selbstverlöschend nach UL94 Kriechstromfestigkeit CTI 600 Halogenfrei Sicherungsaufnahmekontakte: E-Cu, versilbert, fremdbefedert
Degree of protection, Front side device fitted with clamp- IP20C and lateral cover:	
Applicable for fuse-links:	NH000, NH00
Cable terminal:	Universal terminal M8 / 2 x M5
Type of installation:	Baseplate mounting
Poles:	3
Fuse monitoring:	None
Hight:	195 mm
Width:	106 mm
Depth:	84 mm
Direction of cable terminal:	variable
ETIM - Code:	EC001040

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website <http://www.jeanmueller.de>

Printed at: 27.03.2026 / 15:27

Parts list

Spare part:



Type designation: D-KETO-00-3

Article number: T8058012

Description

Handle D-KETO-00-3
 Fuse handle for KETO size 00,
 3pole

Documents



Catalogue



Catalogue Appendix



Operating manual

